

BEFORE YOU BEGIN

Read these instructions and check to be sure all parts and tools are accounted for. Please retain these installation instructions for future reference.

The Rear Windshield is exclusively designed for your vehicle. Please read the installation instructions thoroughly before beginning. Installation is easier if the vehicle is clean and free of debris. For your safety, and to ensure a satisfactory installation, perform all installation steps correctly in the sequence shown.

INSTALLATION INSTRUCTIONS

Note: Shift vehicle transmission into "PARK". Turn key to "OFF" position and remove from vehicle.

Product and accessories picture:



1. Assemble the PC boards with 14 M6*20 socket head cap screws, 7 brackets #4 and 7 brackets #5, and install bracket #4 on the outside. As shown in picture:





2. Put the rear windshield to the rear of the frame according to the position shown in the picture, and then fix the lower end of the rear windshield to the rear frame with four M6*20 hexagon socket head cap screws, four M6 anti-loosening nuts, and two brackets #6 and two brackets #7. As shown in picture:



Rear Windshield for Honda Talon 1000X-4

ZP-YJ-030911-015







3. Secure the rear windshield to the rear post of the frame with four large straps and two small straps and complete the installation.



Note: Please refer to the installation video in the Amazon listing before your installation, or contact the seller for the installation video.