Front Bumper for E-Z-GO RXV Golf Cart

ZP-YJ-041306-001



BEFORE YOU BEGIN

Read these instructions and check to be sure all parts and tools are accounted. Please retain these installation instructions for future reference.

This *front bumper* is exclusively designed for your vehicle. Please read the installation instructions thoroughly before beginning. Installation is easier if the vehicle is clean and free of debris.

PRODUCT AND ACCESSORIES



end of part 1 using two M8*45 Allen screws and two M8 lock nuts.



INSTALLATION INSTRUCTIONS

M8 lock nuts, as shown in the picture:

- Shift vehicle transmission into "PARK". Turn key to "OFF" position and remove from vehicle.
 Assemble the four sleeves (part 4) and part 1 with four M8*45 hex socket screws and four
- 3. Assemble part 3L and part 3R to the lower left and right ends of part 1 using two M8*45 Allen screws and two M8 lock nuts, as shown in the figure. Then, assemble part 2 to the lower

4. Assemble part 5 and part 1 through four sleeves (part 6) using eight M8*50 hex socket screws and eight M8 lock nuts, and then tighten all the screws and nuts. Then install the cover plate part 7 onto the front bumper with three M6*16 hex socket screws, three M6 lock nuts and three M6 flat washers, as shown in the figure:



5. Remove the two nuts that connect the plastic part at the lower end of the golf cart and take off the plastic part.

Front Bumper for E-Z-GO RXV Golf Cart

ZP-YJ-041306-001





6. Install the upper end of the front bumper onto the front frame with two M10 lock nuts, as shown in the illustration:







7. Install the lower end of the front bumper to the lower front of the frame with two M10*65 external hexagon screws with washers and two M10 lock nuts, as shown in the figure. Tighten all the screws and nuts. The installation is completed.





Note: Please refer to the installation video in the Amazon listing before your installation, or contact the seller for the installation video.