

Front Bumper Guard for Club Car Tempo

ZP-YJ-041906-003

SAUTV5

BEFORE YOU BEGIN

Read these instructions and check to be sure all parts and tools are accounted. Please retain these installation instructions for future reference.

This *Front Bumper Guard* is exclusively designed for your vehicle. Please read the installation instructions thoroughly before beginning. Installation is easier if the vehicle is clean and free of debris.

Note: Please refer to the installation video in the Amazon listing before your installation, or contact the seller for the installation video.

PRODUCT



INSTALLATION INSTRUCTIONS

1. Shift vehicle transmission into "PARK". Turn key to "OFF" position and remove from vehicle.
2. Assemble Part 1 and Part 2 using four M8x45 hex socket screws and four M8 lock nuts, with two spacer sleeves (Part 3). As shown:



3. Connect the lower mounting plate of the front bumper using four M8x20 flange hex bolts with bracket (Part 6), as shown:

4. Secure the mesh panel (Part 4) and mesh panel (Part 5) to the front bumper using eight M6x16 hex socket screws, eight M6 flat washers, and eight M6 lock nuts, as shown:



Front Bumper Guard for Club Car Tempo

ZP-YJ-041906-003

5. Remove the two M8x95 hex head screws and two M8 nuts from the original plastic front bumper, then detach the plastic bumper (keep the screws and nuts as spares).



6. Use the two M8x95 hex socket screws and two M8 nuts just removed to install the front bumper onto the lower end of the vehicle frame. Tighten the screws, and the installation is complete.

